













## CERTIFICATION AND CLASSIFICATION Novia

Type of flooring	EN 651	Vinyl floor covering
CE certification		 yes
Classification	ISO 10874 (EN 685)	  Commercial: 34 Industrial: 42

## TECHNICAL CHARACTERISTICS STANDARD Novia

Extreme protection PUR reinforcement		yes
Total thickness	ISO 24346 (EN 428)	 2,2 mm
Wear layer thickness	ISO 24340 (EN 429)	 0,9 mm
Total weight	ISO 23997 (EN 430)	 2,4 kg/m <sup>2</sup>
Form of delivery - Rolls	ISO 24341 (EN 426)	 25 lm (15-25 lm) x 2 m
Wear layer binder content		Type 1

## TECHNICAL PERFORMANCES STANDARD Novia Equipment by standard

Dimensional stability	ISO 23999 (EN 434)	 < 0,4 % Tarkett result: ≤ 10,021 %
Reaction to fire	EN 13501-1	 Bfl-s1
Residual indentation	ISO 24343-1 (EN 433)	 ≤ 0,1 mm
Impact sound reduction	ISO 717/2	 10 dB
Thermal resistance	EN 12524	0,01-0,02 m <sup>2</sup> K/W
Underfloor heating		 Suitable provided that the surface of the subfloor does not exceed 27°C
Fungi and bacteria resistance		Does not contribute to infection spreading
Slip resistance / Ramp test	DIN 51130	R 10
Furniture leg	EN 424	Pass
Castor chair test	ISO 4918 (EN 425)	Pass
Light fastness	ISO 105 B02 - Method 3	≥ 6
Static electrical propensity	EN 1815	≤ 2 kV (antistatic)



	   	Manufactured by: Tarkett d.o.o. Bačka Palanka Industrijska zona 14 21400 Bačka Palanka SERBIA
---	---	---