

## Carousel Felt

<b>Tuft gauge</b>	5/32 cut pile		ISO 2424
<b>Pilecomposition</b>	100% PP		ISO 2424
<b>Primary Backing</b>	Woven		ISO 2424
<b>Secondary backing</b>	Felt		ISO 2424
<b>Width</b>	400 cm, 500 cm	± 1%	EN 984
<b>Pile Weight</b>	890 gr/m <sup>2</sup>		ISO 8543
<b>Total weight</b>	Felt : 1800 gr/m <sup>2</sup>	± 15%	ISO 8543
<b>Pile height</b>	10 mm	± 2 mm	ISO 1766
<b>Total Height</b>	Felt : 13 mm		ISO 1765
<b>Number of knots</b>	112.950/m <sup>2</sup>	-7.5% .+10%	ISO 1763
<b>Fire Classification</b>	Efl	EN 13501-1	
<b>Use Area</b>	Heavy domestic use (23)		EN 1307
<b>GUT Nr.</b>	EFDA4AA3 GUT		www.pro-dis.info
<b>Light fastness</b>	≥ 5		105-B02
<b>Wearebility</b>	≥ 4		105-X12
<b>Water fastness</b>	≥ 4		105-E01

## Floorsymbols



## Certificates



2006  
 Condor Carpets  
 Euroweg 3  
 8061 SB Hasselt  
 EN1307  
 DOP: C-001FC007  
 Reaction to fire:  
 Efl  
 Slip resistance: DS  
 Resilient floor  
 covering to be  
 used within a  
 building

